

RECEIVED
CENTRAL FAX CENTER

FEB 22 2007

Application No. 10/800,131
Filed: March 12, 2004
TC Art Unit: 3644
Confirmation No.: 6931THE CLAIMS

1. (Currently Amended) An aerial vehicle recovery system for a lightweight aerial vehicle having a landing element extending downwardly therefrom, comprising:

a landing pad configured to be supported supportable on a supporting surface, the landing pad comprising a base and an upwardly facing capture surface comprising a passive retaining medium, and a securing system for removably affixing the landing pad to the supporting surface; and

a shoe configured to be mounted removably mountable to a the landing element of an the aerial vehicle, the shoe comprising a base, a passive retaining medium fixed thereto to and supported by a lower surface of the base, and a fastening system for removably fastening the shoe to the landing element of the aerial vehicle, and the passive retaining medium configured to interface interfaces with the passive retaining medium of the landing pad to retain the aerial vehicle directly to the landing pad with no further forward motion component of the vehicle with respect to the landing pad upon affixation.

2. (Currently Amended) The system of claim 1, wherein the landing pad further comprises a base, and the passive retaining medium of the landing pad comprises a passive engagement component supported by the base.

3. (Original) The system of claim 2, wherein the passive engagement system component of the landing pad extends from a substrate supported by the base.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

4. (Original) The system of claim 3, wherein the passive engagement system component of the landing pad comprises a plurality of stems extending from the substrate.
5. (Original) The system of claim 3, wherein the substrate is affixed to an upper surface of the base of the landing pad.
6. (Original) The system of claim 3, wherein the substrate is integrally formed with the base of the landing pad.
7. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a passive engagement component.
8. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a sticky medium.
9. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a tape.
10. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises an adhesive.
11. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad comprises a putty.
12. (Currently Amended) The system of claim 1, wherein ~~the shee~~ further comprises a base and the passive retaining medium of the

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

shoe comprises a passive engagement component supported by the base.

13. (Original) The system of claim 12, wherein the passive engagement system component of the shoe extends from a substrate supported by the base.

14. (Original) The system of claim 13, wherein the passive engagement system component of the shoe comprises a plurality of stems extending from the substrate.

15. (Currently Amended) The system of claim 13, wherein the substrate is affixed to a the lower surface of the base of the shoe.

16. (Original) The system of claim 13, wherein the substrate is integrally formed with the base of the shoe.

17. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a passive engagement component.

18. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a sticky medium.

19. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a tape.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

20. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises an adhesive.

21. (Original) The system of claim 1, wherein the passive retaining medium of the shoe comprises a putty.

22. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise self-engaging fasteners.

23. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise hook and loop fasteners.

24. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise hook-to-hook fasteners.

25. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise stems each having a stalk terminating with a hook.

26. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise stems each having a stalk terminating with a cap.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

27. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise an elastomeric material.

28. (Original) The system of claim 1, wherein the passive retaining medium of the landing pad and the passive retaining medium of the shoe comprise a polyolefin material.

29. (Currently Amended) The system of claim 1, wherein ~~the landing pad further comprises a~~ the base of the landing pad including includes load carrying members ~~operative to transfer for transferring~~ a load on the landing pad to a supporting surface.

30. (Original) The system of claim 29, wherein the base of the landing pad comprises a composite material comprising the load carrying members embedded in a matrix material.

31. (Original) The system of claim 30, wherein the matrix material comprises a polyurethane material.

32. (Original) The system of claim 29, wherein the load carrying members are oriented unidirectionally.

33. (Original) The system of claim 29, wherein the load carrying members comprise a fiberglass material.

34. (Original) The system of claim 29, wherein the load carrying members comprise rods.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

35. (Original) The system of claim 29, wherein the load carrying members comprise flexible straps.

36. (Original) The system of claim 1, wherein the landing pad is rollable.

37. (Withdrawn) The system of claim 1, wherein the landing pad is foldable.

38. (Original) The system of claim 1, wherein the landing pad is flexible.

39. (Original) The system of claim 1, wherein the landing pad is resilient.

40. (Original) The system of claim 1, wherein the landing pad is energy-absorbing.

41. (Original) The system of claim 1, wherein the landing pad further comprises a plurality of pad sections and one or more joint fittings configured to attach the plurality of pad sections together.

42. (Original) The system of claim 41, further comprising load carrying members extending transversely across joints between the pad sections.

43. (Original) The system of claim 41, wherein the joint fittings comprise hinged joint fittings.

Application No. 10/800,131
Filed: March 12, 2004
TC Art Unit: 3644
Confirmation No.: 6931

44. (Original) The system of claim 41, wherein the joint fittings are removably affixed to the pad sections.

45. (Original) The system of claim 1, wherein the landing pad further comprises a plurality of pad sections and a joint attachment mechanism configured to attach the plurality of pad sections together.

46. (Withdrawn) The system of claim 1, wherein the landing pad further comprises a plurality of pad sections attached together along hinged joints.

47. (Withdrawn) The system of claim 46, wherein the hinged joints are integral with the pad sections.

48. (Withdrawn) The system of claim 46, wherein the hinged joints are permanently affixed to the pad sections.

49. (Withdrawn) The system of claim 46, wherein the hinged joints are removably affixed to the pad sections.

50. (Withdrawn) The system of claim 1, wherein the landing pad further includes an energy-absorbing layer.

51. (Withdrawn) The system of claim 1, wherein the landing pad further includes an energy-absorbing layer between two panels.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

52. (Withdrawn) The system of claim 51, wherein the panels comprise panel sections, and the panel sections of one of the panels are attached together along hinged joints

53. (Withdrawn) The system of claim 51, wherein the panels are rigid.

54. (Withdrawn) The system of claim 51, wherein the panels are semi-rigid.

55. (Withdrawn) The system of claim 1, wherein the landing pad further comprises a panel having first and second sides and energy-absorbing legs affixed to the first side of the panel, and the passive retaining medium is supported by the second side of the panel.

56. (Withdrawn) The system of claim 55, wherein the panel comprises panel sections attached together along hinged joints.

57. (Currently Amended) The system of claim 1, wherein the landing pad further includes:

load carrying members operative to transfer a load on the landing pad to a supporting surface; and

a the securing system is in load transferring communication with the load carrying members ~~and configured to affix the landing pad to a supporting surface.~~

58. (Original) The system of claim 57, wherein the securing system comprises fittings disposed along edges of the landing pad.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

59. (Original) The system of claim 58, wherein the fittings are removably attachable along edges of the landing pad.

60. (Original) The system of claim 58, wherein the fittings comprise clamp mechanisms attachable along edges of the landing pad.

61. (Original) The system of claim 58, wherein the fittings are permanently affixed along edges of the landing pad.

62. (Original) The system of claim 57, wherein the securing system comprises fittings having rope or strap attachment components.

63. (Original) The system of claim 62, wherein the rope or strap attachment components comprise rings, loops, or eyes.

64. (Original) The system of claim 1, wherein the shoe is elongated from a front end to a back end and curved from the front end to the back end.

65. (Cancelled) ~~The system of claim 1, wherein the shoe further comprises a base, the passive retaining medium supported by the base.~~

66. (Withdrawn) The system of claim 65, wherein the base of the shoe comprises a flat pad.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

67. (Original) The system of claim 65, wherein the base of the shoe is rigid.

68. (Original) The system of claim 65, wherein the base of the shoe is semi-rigid.

69. (Original) The system of claim 65, wherein the base of the shoe is flexible.

70. (Canceled) ~~The system of claim 1, further comprising a fastening system configured to fasten the shoe to the lowermost landing element of the aerial vehicle.~~

71. (Currently Amended) The system of claim ~~70~~ 1, wherein the fastening system comprises at least one pair of upwardly extending tabs on opposed sides of the shoe and a fastening element fastenable between the tabs of a pair of tabs.

72. (Withdrawn) The system of claim 70, wherein the fastening system comprises a hose clamp.

73. (Original) The system of claim 1, further comprising a transport cart configured to store and transport the landing pad.

74. (Original) The system of claim 1, further comprising a transport cart configured to transport the aerial vehicle.

-11-

WEINGARTEN, SCHURGIN,
GAGNERIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

75. (Original) The system of claim 74, wherein the transport cart includes a hoist mechanism configured to hoist the aerial vehicle onto the transport cart.

76. (Original) The system of claim 74, wherein the transport cart includes a jack mechanism configured to jack the aerial vehicle onto the transport cart.

77. (Original) The system of claim 1, wherein the landing pad is securable to a ship's deck.

78. (Original) The system of claim 1, wherein the landing pad is secured to a ship's deck.

79. (Original) The system of claim 1, wherein the landing pad is securable to a truck bed.

80. (Original) The system of claim 1, wherein the landing pad is secured to a truck bed.

81. (Original) The system of claim 1, wherein the landing pad is securable to an offshore platform.

82. (Original) The system of claim 1, wherein the landing pad is secured to an offshore platform.

83. (Original) The system of claim 1, wherein the landing pad is securable to ground.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

84. (Original) The system of claim 1, wherein the landing pad is secured to ground.

85. (Withdrawn) A method for recovering an aerial vehicle using the recovery system of claim 1 comprising:

providing the landing pad on a support surface; and

landing the aerial vehicle with the shoe mounted on the lowermost landing element on the landing pad with the passive retaining medium of the landing pad and the passive retaining medium of the shoe in retention.

86. (Withdrawn) The method of claim 85, further comprising:

removing the shoe from the aerial vehicle while the vehicle is on the landing pad; and

removing the aerial vehicle from the landing pad, leaving the shoe engaged on the landing pad.

87. (Withdrawn) A method for recovering an aerial vehicle comprising:

providing a landing pad configured to be supported on a supporting surface, the landing pad comprising an upwardly facing capture surface comprising a passive retaining medium; and

landing the aerial vehicle on the landing pad, a landing element of the aerial vehicle retained by the passive retaining medium on the capture surface.

88. (Withdrawn) An aerial vehicle recovery system comprising:
an aerial vehicle having a landing element; and

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

a passive retaining medium mounted to the landing element and configured to retain the aerial vehicle on a landing surface.

89. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises a passive engagement component.

90. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises a hook-to-hook fastener.

91. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises a hook and loop fastener.

92. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises tape.

93. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises adhesive.

94. (Withdrawn) The system of claim 88, wherein the passive retaining medium comprises putty.

95. (Withdrawn) The system of claim 88, wherein the passive retaining medium is adhesively mounted to the landing element.

96. (Withdrawn) The system of claim 88, wherein the passive retaining medium is removably mounted to the landing element.

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

97. (Withdrawn) The system of claim 88, wherein the passive retaining medium is affixed to a shoe mounted to the landing element.

98. (Withdrawn) The system of claim 97, wherein the shoe is removably mounted to the landing element.

99. (Withdrawn) A method for recovering an aerial vehicle using the recovery system of claim 88, comprising:

landing the aerial vehicle with the passive retaining medium on the landing element of the aerial vehicle in retention with the landing surface.

100. (Withdrawn) The method of claim 99, wherein the landing surface comprises a ship's deck.

101. (Withdrawn) The method of claim 99, wherein the landing surface comprises a truck bed.

102. (Withdrawn) The method of claim 99, wherein the landing surface comprises an offshore platform.

103. (Withdrawn) The method of claim 99, wherein the landing surface comprises ground.

104. (Withdrawn) The method of claim 99, wherein the landing surface comprises a landing pad.

-15-

WEINGARTEN, SCHURGIN,
GAGNEBIN & LEBOVICI LLP
TEL. (617) 542-2290
FAX. (617) 451-0313

Application No. 10/800,131

Filed: March 12, 2004

TC Art Unit: 3644

Confirmation No.: 6931

105. (Withdrawn) The method of claim 99, further comprising providing the landing surface with a passive retaining medium thereon.

106. (Withdrawn) The method of claim 105, wherein the landing surface has a hook and loop fastener thereon.

107. (Withdrawn) The method of claim 105, wherein the landing surface has a hook-to-hook fastener thereon.

108. (Withdrawn) The method of claim 105, wherein the landing surface has tape thereon.

109. (Withdrawn) The method of claim 105, wherein the landing surface has adhesive thereon.

110. (Withdrawn) The method of claim 105, wherein the landing surface has putty thereon.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.